NSN 5985-01-216-5796

Fixed Attenuator - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5985-01-216-5796



Application Design:

Transmission line

Body Material:

Steel, stainless

Body Style:

1b round, terminal/terminals in opposite surface

Body Surface Treatment:

Any acceptable

Overall Length:

0.860 inches

Overall Diameter:

0.280 inches

Operating Tempurature Range:

-65.0 to 125.0 degrees celsius

Voltage Standing Wave Ratio:

1.07

Input Impedance Rating In Ohms:

50.0

Output Impedance Rating In Ohms:

50.0

Coaxial Connector Series Designation:

Sma

Power Rating:

2.0 watts average

Rf Signal Attenuation In Decibels:

1.0

Voltage Standing Wave Ratio Frequency Range:

+0.0 to 12.4 gigahertz

Attenuation Accuracy Reference Frequency:

12.4 gigahertz

Attenuation Accuracy In Decibels:

-0.30 to 0.30

Connection Type Per Function:

Female output and male input

Mounting Method:

Connector

Terminal Type And Quantity:

2 connector

Frequency Range:

Between 0.000 hertz and 12.400 gigahertz

Fsc Application Data:

Antennas, waveguides, and related equipment

NSN 5985-01-216-5796

Fixed Attenuator - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A20000

