## NSN 5985-01-216-8561

Fixed Attenuator - Page 1 of 2

Gold

N/a

Shelf Life:



View Online at https://aerobasegroup.com/nsn/5985-01-216-8561 **Application Design:** Transmission line **Body Material:** Steel, stainless **Body Style:** 1b round, terminal/terminals in opposite surface **Body Surface Treatment:** Passivated **Overall Length:** 0.750 inches **Overall Diameter:** 0.312 inches **Operating Tempurature Range:** -55.0 to 125.0 degrees celsius **Voltage Standing Wave Ratio:** 1.15 and 1.25 and 1.50 and 1.80 and 2.00 Input Impedance Rating In Ohms: 50.0 **Output Impedance Rating In Ohms:** 50.0 **Coaxial Connector Series Designation:** Sma **Power Rating:** 2.0 watts average Rf Signal Attenuation In Decibels: 20.0 **Voltage Standing Wave Ratio Frequency Range:** +0.0 to 4.0 gigahertz and +4.1 to 8.0 gigahertz and +8.1 to 12.0 gigahertz and +12.1 to 15.0 gigahertz and +15.1 to 18.0 gigahertz **Mounting Method:** Connector **Terminal Type And Quantity:** 2 connector Frequency Range: Between 0.000 hertz and 18.000 gigahertz **Special Features:** Fungus test per mil-std-810 method 508; salt atmosphere mil-std-202 method 101 cond a **Precious Material And Location:** Pin surface gold **Precious Material:** 

## NSN 5985-01-216-8561

Fixed Attenuator - Page 2 of 2



	Of			

--

Demilitarization:

No

Fiig:

A20000