

View Online at <https://aerobasegroup.com/nsn/5985-01-216-8561>

**Application Design:**

Transmission line

**Body Material:**

Steel, stainless

**Body Style:**

1b round, terminal/terminals in opposite surface

**Body Surface Treatment:**

Passivated

**Overall Length:**

0.750 inches

**Overall Diameter:**

0.312 inches

**Operating Temperature Range:**

-55.0 to 125.0 degrees celsius

**Voltage Standing Wave Ratio:**

1.15 and 1.25 and 1.50 and 1.80 and 2.00

**Input Impedance Rating In Ohms:**

50.0

**Output Impedance Rating In Ohms:**

50.0

**Coaxial Connector Series Designation:**

Sma

**Power Rating:**

2.0 watts average

**Rf Signal Attenuation In Decibels:**

20.0

**Voltage Standing Wave Ratio Frequency Range:**

+0.0 to 4.0 gigahertz and +4.1 to 8.0 gigahertz and +8.1 to 12.0 gigahertz and +12.1 to 15.0 gigahertz and +15.1 to 18.0 gigahertz

**Mounting Method:**

Connector

**Terminal Type And Quantity:**

2 connector

**Frequency Range:**

Between 0.000 hertz and 18.000 gigahertz

**Special Features:**

Fungus test per mil-std-810 method 508; salt atmosphere mil-std-202 method 101 cond a

**Precious Material And Location:**

Pin surface gold

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A20000