NSN 5985-01-218-9970

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-218-9970

Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
2.250 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.594 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
0.844 inches
Overall Height:
1.000 inches
Overall Width:
2.000 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.500 inches
Voltage Standing Wave Ratio:
1.50
Coaxial Connector Series Designation:
Sma
Power Rating:
5.0 watts average
Mounting Facility Screw Thread Series Designator:
Unc
Insertion Loss At Minimum Attenuation In Maximum Decibels:
0.5
Overall Attenuation Range In Decibels:
+0.0 to 30.0
Attenuation Variation Method:
Continuous
Mounting Facility Type And Quantity:
4 threaded hole
Frequency Range:
Between 7.250 gigahertz and 8.400 gigahertz
Overall Attenuation Accuracy In Decibels:
-0.50 to 0.50
Mounting Thread Quantity:
40 per inch
Adjustment Device Type And Quantity:

1 shaft

NSN 5985-01-218-9970

Variable Attenuator - Page 2 of 2



Mounting Facility Pattern: Four position rectangular Shaft Type: Round, slotted Mounting Facility Screw Thread Diameter: 0.112 inches Impedance Rating In Ohms: 50.0 input-output Terminal Type And Quantity: 2 connector, coaxial, male Shelf Life: N/a Unit Of Measure: -Demilitarization:

Yes - demil/mli

Fiig: A223a0