NSN 5985-01-222-0021

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-222-0021

Application Design:

Transmission line

Body Material:

Beryllium copper

Body Style:

Rectangular terminal/terminals on three surfaces

Body Surface Treatment:

Gold plated, mil-g-45204

Overall Length:

0.750 inches

Overall Height:

0.150 inches

Overall Width:

0.515 inches

Operating Tempurature Range:

-55.0 to 150.0 degrees celsius

End Application:

5895-00-222-4224 communications set

Voltage Standing Wave Ratio:

1.15 and 1.35 and 1.50

Input Impedance Rating In Ohms:

50.0

Output Impedance Rating In Ohms:

50.0

Power Rating:

20.0 watts average

Rf Signal Attenuation In Decibels:

4.0

Voltage Standing Wave Ratio Frequency Range:

+0.0 to 1.0 gigahertz and +1.0 to 2.5 gigahertz and +2.5 to 4.0 gigahertz

Attenuation Accuracy In Decibels:

-0.50 to 0.50

Mounting Method:

Terminal

Terminal Type And Quantity:

2 ribbon and 1 surface contact

Frequency Range:

Between 0.000 hertz and 4.000 gigahertz

Precious Material And Location:

Terminals gold

Precious Material:

Gold

NSN 5985-01-222-0021

Fixed Attenuator - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A20000

