## NSN 5985-01-222-0022

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-222-0022

Application Design:
Transmission line
Body Material:
Beryllium copper
Body Style:
Rectangular terminal/terminals on three surfaces
Body Surface Treatment:
Gold plated, mil-g-45204
Overall Length:
0.750 inches
Overall Height:
0.150 inches
Overall Width:
0.515 inches
Operating Tempurature Range:
-55.0 to 150.0 degrees celsius
End Application:
5895-00-222-4224 communication set
Voltage Standing Wave Ratio:
1.15 and 1.35 and 1.50
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Power Rating:
20.0 watts average
Rf Signal Attenuation In Decibels:
1.0
Voltage Standing Wave Ratio Frequency Range:
+0.0 to 1.0 gigahertz and +1.0 to 2.5 gigahertz and +2.5 to 4.0 gigahertz
Attenuation Accuracy In Decibels:
-0.50 to 0.50
Mounting Method:
Terminal
Terminal Type And Quantity:
2 ribbon and 1 surface contact
Frequency Range:
Between 0.000 hertz and 4.000 gigahertz
Precious Material And Location:
Terminals gold
Precious Material:
i recious materiai.

Gold

## NSN 5985-01-222-0022

Fixed Attenuator - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A20000