## NSN 5985-01-222-9226

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-222-9226 **Application Design:** Transmission line **Body Material:** Steel, stainless **Body Style:** 1b round, terminal/terminals in opposite surface **Body Surface Treatment:** Passivated **Overall Length:** 1.250 inches **Overall Diameter:** 0.380 inches **Operating Tempurature Range:** -46.0 to 125.0 degrees celsius **End Application:** 1430-01-087-6330 radar set **Voltage Standing Wave Ratio:** 1.20 **Input Impedance Rating In Ohms:** 50.0 **Output Impedance Rating In Ohms:** 50.0 **Coaxial Connector Series Designation:** Sma **Power Rating:** 2.0 watts average **Rf Signal Attenuation In Decibels:** 4.0 **Voltage Standing Wave Ratio Frequency Range:** +4.0 to 6.0 gigahertz **Attenuation Accuracy In Decibels:** -0.30 to 0.30 **Mounting Method:** Connector **Terminal Type And Quantity:** 2 connector Frequency Range: Between 0.000 hertz and 12.400 gigahertz Shelf Life: N/a

--

**Unit Of Measure:** 

## NSN 5985-01-222-9226

Fixed Attenuator - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A20000