

View Online at <https://aerobasegroup.com/nsn/5985-01-223-3671>

**Body Style:**

Rectangular

**Overall Length:**

2.648 inches

**Overall Height:**

2.020 inches

**Overall Width:**

1.320 inches

**Frequency Rating:**

0.0 megahertz and 1000.0 megahertz single frequency voltage standing wave ratio

**Unthreaded Mounting Hole Diameter:**

0.141 inches

**Switch Type:**

Transfer

**Longest Horizontal Distance Between Mounting Centers:**

1.650 inches single mounting facility pattern

**Longest Vertical Distance Between Mounting Centers:**

0.800 inches single mounting facility pattern

**Operating Temperature Range:**

-55.0 to 85.0 degrees celsius

**Voltage Standing Wave Ratio:**

1.10 single

**Insertion Loss In Decibels:**

0.15 single

**Coaxial Connector Series Designation:**

Sma

**Connector End Design:**

Female

**Rf Power Handling Capability:**

65.0 watts peak single

**Minimum Crosstalk Rating In Decibels:**

80.0 single

**Actuator Operating Method:**

Relay

**Actuator Voltage In Volts:**

28.0

**Switch Operation Sequence:**

Breaks before makes

**Switching Time:**

20.0 milliseconds

**Switch Return Mechanism Type:**

Fail-safe

**Coupling Position Quantity:**

4

**Mounting Facility Type And Quantity:**

3 unthreaded hole

**Mounting Facility Pattern:**

Isosceles triangle single mounting facility pattern

**Special Features:**

Continuous duty cycle; operational life 1, 000, 000 operations

**Material:**

Aluminum body

**Surface Treatment:**

Chromate body outside surfaces

**Terminal Type And Quantity:**

5 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A158a0