

View Online at <https://aerobasegroup.com/nsn/5985-01-223-3671>

Body Style:

Rectangular

Overall Length:

2.648 inches

Overall Height:

2.020 inches

Overall Width:

1.320 inches

Frequency Rating:

0.0 megahertz and 1000.0 megahertz single frequency voltage standing wave ratio

Unthreaded Mounting Hole Diameter:

0.141 inches

Switch Type:

Transfer

Longest Horizontal Distance Between Mounting Centers:

1.650 inches single mounting facility pattern

Longest Vertical Distance Between Mounting Centers:

0.800 inches single mounting facility pattern

Operating Temperature Range:

-55.0 to 85.0 degrees celsius

Voltage Standing Wave Ratio:

1.10 single

Insertion Loss In Decibels:

0.15 single

Coaxial Connector Series Designation:

Sma

Connector End Design:

Female

Rf Power Handling Capability:

65.0 watts peak single

Minimum Crosstalk Rating In Decibels:

80.0 single

Actuator Operating Method:

Relay

Actuator Voltage In Volts:

28.0

Switch Operation Sequence:

Breaks before makes

Switching Time:

20.0 milliseconds

Switch Return Mechanism Type:

Fail-safe

Coupling Position Quantity:

4

Mounting Facility Type And Quantity:

3 unthreaded hole

Mounting Facility Pattern:

Isosceles triangle single mounting facility pattern

Special Features:

Continuous duty cycle; operational life 1, 000, 000 operations

Material:

Aluminum body

Surface Treatment:

Chromate body outside surfaces

Terminal Type And Quantity:

5 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A158a0