## NSN 5985-01-223-5245

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-223-5245

| c atpon/ao.ocacog.ocap.co                        |
|--|
| Application Design:                              |
| Transmission line                                |
| Body Style:                                      |
| 1b round, terminal/terminals in opposite surface |
| Overall Length:                                  |
| Between 0.830 inches and 0.890 inches            |
| Overall Diameter:                                |
| 0.280 inches                                     |
| Operating Tempurature Range:                     |
| -40.0/+71.0 degrees celsius                      |
| Voltage Standing Wave Ratio:                     |
| 1.35   |
| Input Impedance Rating In Ohms:                  |
| 50.0   |
| Output Impedance Rating In Ohms:                 |
| 50.0   |
| Coaxial Connector Series Designation:            |
| Sma  |
| Rf Signal Attenuation In Decibels:               |
| 1.0  |
| Voltage Standing Wave Ratio Frequency Range:     |
| +13.5/+17.0 gigahertz                            |
| Attenuation Accuracy In Decibels:                |
| -0.30/+0.30                                      |
| Connection Type Per Function:                    |
| Female input and male output                     |
| Unpackaged Unit Weight:                          |
| 0.187 ounces                                     |
| Mounting Method:                                 |
| Connector  |
| Terminal Type And Quantity:                      |
| 2 connector                                      |
| Frequency Range:                                 |
| Between 13.500 gigahertz and 17.000 gigahertz    |
| Special Features:                                |
| Oper alt 40000 ft                                |
| Fsc Application Data:                            |
| Antennas, waveguides, and related equipment      |
| Shelf Life:                                      |
| N/a  |
| Unit Of Measure:                                 |
|  |

--

## NSN 5985-01-223-5245

Fixed Attenuator - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A20000