## NSN 5985-01-223-5245

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-223-5245

c atpos//ao.ocacog.ocap.co
Application Design:
Transmission line
Body Style:
1b round, terminal/terminals in opposite surface
Overall Length:
Between 0.830 inches and 0.890 inches
Overall Diameter:
0.280 inches
Operating Tempurature Range:
-40.0/+71.0 degrees celsius
Voltage Standing Wave Ratio:
1.35
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
Sma
Rf Signal Attenuation In Decibels:
1.0
Voltage Standing Wave Ratio Frequency Range:
+13.5/+17.0 gigahertz
Attenuation Accuracy In Decibels:
-0.30/+0.30
Connection Type Per Function:
Female input and male output
Unpackaged Unit Weight:
0.187 ounces
Mounting Method:
Connector
Terminal Type And Quantity:
2 connector
Frequency Range:
Between 13.500 gigahertz and 17.000 gigahertz
Special Features:
Oper alt 40000 ft
Fsc Application Data:
Antennas, waveguides, and related equipment
Shelf Life:
N/a
Unit Of Measure:

--

## NSN 5985-01-223-5245

Fixed Attenuator - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A20000