## NSN 5985-01-223-9427

**Thread Class:** 

2b mounting facility hole

Radio Frequency Transmission Line Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-223-9427

| Frequency Rating:   |
|---|
| 8.5 gigahertz single frequency operating and 9.6 gigahertz single frequency operating |
| Switch Type:  |
| Nontransfer   |
| Voltage Standing Wave Ratio:  |
| 1.10 single   |
| Insertion Loss In Decibels:   |
| 0.25 single   |
| Rf Power Handling Capability:   |
| 500.0 watts average 2nd   |
| Minimum Crosstalk Rating In Decibels:   |
| 60.0 single   |
| Actuator Operating Method:  |
| Relay   |
| Actuator Current Type And Rating In Amps:   |
| Between 1.5 dc and 2.0 dc   |
| Actuator Voltage In Volts:  |
| 28.0  |
| Switch Operation Sequence:  |
| Breaks before makes   |
| Switch Return Mechanism Type:   |
| Fail-safe   |
| Pole Quantity:  |
| 1   |
| Throw Quantity:   |
| 2   |
| Coupling Position Quantity:   |
| 3   |
| Mounting Facility Type And Quantity:  |
| 16 threaded hole  |
| Thread Size:  |
| 0.164 inches mounting facility hole   |
| Thread Series Designator:   |
| Unc mounting facility hole  |
| Terminal Type And Quantity:   |
| 1 connector, receptacle and 3 rectangular flange                                      |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |

## NSN 5985-01-223-9427

Radio Frequency Transmission Line Switch - Page 2 of 2



Demilitarization:

No

Fiig:

A158a0