

View Online at <https://aerobasegroup.com/nsn/5985-01-224-3674>

**Body Style:**

Rectangular

**Overall Length:**

2.057 inches

**Overall Height:**

1.750 inches

**Overall Width:**

1.750 inches

**Frequency Rating:**

0.0 gigahertz single frequency operating and 18.0 gigahertz single frequency operating

**Unthreaded Mounting Hole Diameter:**

1.440 inches

**Switch Type:**

Nontransfer

**Longest Horizontal Distance Between Mounting Centers:**

1.375 inches single mounting facility pattern

**Longest Vertical Distance Between Mounting Centers:**

1.375 inches single mounting facility pattern

**Operating Temperature Range:**

-35.0/+55.0 degrees celsius

**End Application:**

Oq-20 (v) 2/msm

**Voltage Standing Wave Ratio:**

1.50 4th

**Insertion Loss In Decibels:**

0.40 3rd

**Coaxial Connector Series Designation:**

Sma

**Connector End Design:**

Female

**Rf Power Handling Capability:**

50.0 watts average single

**Minimum Crosstalk Rating In Decibels:**

70.0 2nd

**Switch Operation Sequence:**

Makes before breaks

**Pole Quantity:**

1

**Throw Quantity:**

6

**Coupling Position Quantity:**

6

**Mounting Facility Type And Quantity:**

1 base and 2 unthreaded hole

**Mounting Facility Pattern:**

Four position rectangular single mounting facility pattern

**Special Features:**

Actuator operating method: solenoid

**Material:**

Aluminum alloy body

**Precious Material And Location:**

Internal surfaces gold

**Precious Material:**

Gold

**Surface Treatment:**

Gold body all surfaces

**Terminal Type And Quantity:**

7 solder stud and 7 receptacle, coaxial

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A158a0