NSN 5985-01-224-7079

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-224-7079

Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
4.312 inches
Overall Height:
1.375 inches
Overall Width:
2.812 inches
Voltage Standing Wave Ratio:
1.20
Coaxial Connector Series Designation:
Bnc
Power Rating:
500.0 milliwatts average and 750.0 watts peak
Mounting Facility Screw Thread Series Designator:
Unc
Overall Attenuation Range In Decibels:
+0.0 to 1.5
Attenuation Variation Method:
Stepped
Step Position Quantity:
4
Attenuation Per Step In Decibels:
0.1
Mounting Facility Type And Quantity:
2 threaded hole
Frequency Range:
Between 0.000 hertz and 500.000 megahertz
Adjustment Device Type And Quantity:
1 electronic, programmable
Mounting Facility Screw Thread Diameter:
0.164 inches
Impedance Rating In Ohms:
50.0 input-output
Terminal Type And Quantity:
2 connector, coaxial, female
Shelf Life:
N/a
Unit Of Measure:

--

NSN 5985-01-224-7079

Variable Attenuator - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A223a0