NSN 5985-01-224-8306

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-224-8306

Cross Sectional Shape:

Internal, rectangular external, rectangular

Bend Angle In Deg:

90.0 single bend h-plane

End Application:

Synchro receiver, r-1979/aps-124 used on sh-60b helicopter lamps mk 3

Tubing Wall Construction Style:

Seamless all tubing segment

Flange Quantity:

2

Flange Inside Width:

1.003 inches and 1.006 inches first flange

Flange Inside Height:

0.503 inches and 0.506 inches first flange

Flange Outside Width:

1.610 inches and 1.640 inches first flange

Flange Outside Height:

1.610 inches and 1.640 inches first flange

Flange Depth:

0.423 inches and 0.453 inches first flange

Flange Connecting Hole Diameter:

0.169 inches and 0.172 inches first flange all connection facilities

Waveguide Outside Width:

Between 0.996 inches and 1.004 inches

Waveguide Inside Width:

Between 0.896 inches and 0.904 inches

Waveguide Inside Height:

Between 0.396 inches and 0.404 inches

Waveguide Outside Height:

Between 0.496 inches and 0.504 inches

Waveguide Longer Offset Distance:

1.250 inches

Flange Connecting Facility And Quantity:

4 unthreaded hole first flange all connection facilities

Flange Style:

Cover type first flange

Waveguide Offset Distance:

1.125 inches

Flexibility:

Rigid all tubing segment

Material:

Aluminum alloy all tubing segment and flange

NSN 5985-01-224-8306

Waveguide Assembly - Page 2 of 2



_	•	_	-			
Ç.	urfac	ו מי	roa	tm	Δn	
υı	ai i a		ıca		CII	L.

Paint all tubing segment and flange outside surfaces

Style Designator:

Bend type

Fsc Application Data:

Antennas, waveguides, and related equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A073a0