NSN 5985-01-228-6968

Fixed Attenuator - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5985-01-228-6968 |
|---|
| Application Design: |
| Transmission line |
| Body Material: |
| Metal |
| Body Style: |
| Err-090 |
| Overall Length: |
| 3.250 inches |
| Overall Diameter: |
| 0.781 inches |
| Operating Tempurature Range: |
| -55.0/+85.0 degrees celsius |
| Voltage Standing Wave Ratio: |
| 1.15 |
| Input Impedance Rating In Ohms: |
| 50.0 |
| Output Impedance Rating In Ohms: |
| 50.0 |
| Coaxial Connector Series Designation: |
| N . |
| Power Rating: |
| 1.0 watts average and 1.0 kilowatts peak |
| Rf Signal Attenuation In Decibels: |
| 30.0 |
| Voltage Standing Wave Ratio Frequency Range: |
| +0.0/+1.5 gigahertz |
| Attenuation Accuracy In Decibels: |
| -0.30/+0.30 |
| Connection Type Per Function: |
| Male input and female output |
| Mounting Method: |
| Connector |
| Terminal Type And Quantity: |
| 2 connector |
| Frequency Range: |
| Between 0.000 hertz and 1.500 gigahertz |
| Test Data Document: |
| 81349-mil-a-3933 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

--

NSN 5985-01-228-6968

Fixed Attenuator - Page 2 of 2



Demilitarization:

No

Fiig:

A20000