NSN 5985-01-228-9810

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-228-9810 **Application Design:** Transmission line **Body Material:** Metal **Body Style:** Err-090 **Overall Length:** 4.375 inches **Overall Diameter:** 0.760 inches **Operating Tempurature Range:** -55.0/+85.0 degrees celsius **Voltage Standing Wave Ratio:** 1.20 Input Impedance Rating In Ohms: 50.0 **Output Impedance Rating In Ohms:** 50.0 **Coaxial Connector Series Designation: Power Rating:** 2.0 watts average and 2.0 kilowatts peak Rf Signal Attenuation In Decibels: 3.0 **Voltage Standing Wave Ratio Frequency Range:** +0.0/+3.0 gigahertz **Attenuation Accuracy In Decibels:** -0.20/+0.20 **Mounting Method:** Connector **Terminal Type And Quantity:** 2 connector Frequency Range: Between 0.000 hertz and 3.000 gigahertz **Test Data Document:** 81349-mil-a-3933 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a

No

Unit Of Measure:

Demilitarization:

NSN 5985-01-228-9810

Fixed Attenuator - Page 2 of 2



Fiig:

A20000

Mil-std (military Standard):

Mil-a-3933 spec.