

View Online at <https://aerobasegroup.com/nsn/5985-01-230-2834>

Application Design:

Transmission line

Body Material:

Metal

Body Style:

1b round, terminal/terminals in opposite surface

Terminal Material:

Steel, stainless

Terminal Surface Treatment:

Passivated

Body Surface Treatment:

Any acceptable

Overall Length:

1.490 inches

Overall Diameter:

0.625 inches

Operating Temperature Range:

-55.0 to 85.0 degrees celsius

Voltage Standing Wave Ratio:

1.25 and 1.40

Input Impedance Rating In Ohms:

50.0

Output Impedance Rating In Ohms:

50.0

Coaxial Connector Series Designation:

Sma

Power Rating:

5.5 watts average and 200.0 watts peak

Rf Signal Attenuation In Decibels:

30.0

Voltage Standing Wave Ratio Frequency Range:

+0.0 to 4.0 gigahertz and +4.0 to 6.0 gigahertz

Attenuation Accuracy Reference Frequency:

6.0 gigahertz

Attenuation Accuracy In Decibels:

-0.50 to 0.50

Connection Type Per Function:

Female input and male output

Unpackaged Unit Weight:

0.500 ounces

Mounting Method:

Connector

Terminal Type And Quantity:

2 connector

Frequency Range:

Between 0.000 hertz and 6.000 gigahertz

Fsc Application Data:

Antennas, waveguides, and related equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A20000