

View Online at <https://aerobasegroup.com/nsn/5985-01-230-2834>

**Application Design:**

Transmission line

**Body Material:**

Metal

**Body Style:**

1b round, terminal/terminals in opposite surface

**Terminal Material:**

Steel, stainless

**Terminal Surface Treatment:**

Passivated

**Body Surface Treatment:**

Any acceptable

**Overall Length:**

1.490 inches

**Overall Diameter:**

0.625 inches

**Operating Temperature Range:**

-55.0 to 85.0 degrees celsius

**Voltage Standing Wave Ratio:**

1.25 and 1.40

**Input Impedance Rating In Ohms:**

50.0

**Output Impedance Rating In Ohms:**

50.0

**Coaxial Connector Series Designation:**

Sma

**Power Rating:**

5.5 watts average and 200.0 watts peak

**Rf Signal Attenuation In Decibels:**

30.0

**Voltage Standing Wave Ratio Frequency Range:**

+0.0 to 4.0 gigahertz and +4.0 to 6.0 gigahertz

**Attenuation Accuracy Reference Frequency:**

6.0 gigahertz

**Attenuation Accuracy In Decibels:**

-0.50 to 0.50

**Connection Type Per Function:**

Female input and male output

**Unpackaged Unit Weight:**

0.500 ounces

**Mounting Method:**

Connector

**Terminal Type And Quantity:**

2 connector

**Frequency Range:**

Between 0.000 hertz and 6.000 gigahertz

**Fsc Application Data:**

Antennas, waveguides, and related equipment

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A20000