NSN 5985-01-230-2834

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-230-2834

Application Design:
Transmission line
Body Material:
Metal
Body Style:
1b round, terminal/terminals in opposite surface
Terminal Material:
Steel, stainless
Terminal Surface Treatment:
Passivated
Body Surface Treatment:
Any acceptable
Overall Length:
1.490 inches
Overall Diameter:
0.625 inches
Operating Tempurature Range:
-55.0 to 85.0 degrees celsius
Voltage Standing Wave Ratio:
1.25 and 1.40
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
Sma
Power Rating:
5.5 watts average and 200.0 watts peak
Rf Signal Attenuation In Decibels:
30.0
Voltage Standing Wave Ratio Frequency Range:
+0.0 to 4.0 gigahertz and +4.0 to 6.0 gigahertz
Attenuation Accuracy Reference Frequency:
6.0 gigahertz
Attenuation Accuracy In Decibels:
-0.50 to 0.50
Connection Type Per Function:
Female input and male output
Unpackaged Unit Weight:
0.500 ounces
Mounting Method:

NSN 5985-01-230-2834 Fixed Attenuator - Page 2 of 2



Terminal Type And Quantity:
2 connector
Frequency Range:
Between 0.000 hertz and 6.000 gigahertz
Fsc Application Data:
Antennas, waveguides, and related equipment
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A20000