

View Online at <https://aerobasegroup.com/nsn/5985-01-230-2975>

**Frequency Rating:**

200.0 megahertz single frequency voltage standing wave ratio and 450.0 megahertz single frequency voltage standing wave ratio

**Unthreaded Mounting Hole Diameter:**

0.093 inches

**Switch Type:**

Nontransfer

**Longest Horizontal Distance Between Mounting Centers:**

2.336 inches single mounting facility pattern

**Longest Vertical Distance Between Mounting Centers:**

1.336 inches single mounting facility pattern

**Voltage Standing Wave Ratio:**

1.25 2nd

**Insertion Loss In Decibels:**

0.50 2nd

**Coaxial Connector Series Designation:**

Sma

**Connector End Design:**

Female

**Switching Time:**

5.0 milliseconds

**Switch Return Mechanism Type:**

Fail-safe

**Pole Quantity:**

1

**Throw Quantity:**

4

**Rf Maximum Voltage Rating:**

12.0 volts peak

**Mounting Facility Type And Quantity:**

1 base and 4 unthreaded hole

**Special Features:**

Actuator operating method: solenoid

**Terminal Type And Quantity:**

5 tab, solder lug and 5 receptacle, coaxial

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A158a0