NSN 5985-01-230-2977

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-230-2977 **Application Design:** Transmission line **Body Material:** Steel, stainless **Body Style:** 1b round, terminal/terminals in opposite surface **Body Surface Treatment:** Passivated **Overall Length:** Between 1.185 inches and 1.245 inches **Overall Diameter:** 0.312 inches **End Application:** 5865-01-107-1039 receiving set, countermeasures **Voltage Standing Wave Ratio:** 1.15 and 1.25 and 1.35 Input Impedance Rating In Ohms: 50.0 **Output Impedance Rating In Ohms:** 50.0 **Coaxial Connector Series Designation:** Sma **Power Rating:** 2.0 watts average **Rf Signal Attenuation In Decibels:** 8.5 **Voltage Standing Wave Ratio Frequency Range:** +0.0 to 8.0 gigahertz and +8.0 to 12.4 gigahertz and +12.4 to 18.0 gigahertz **Attenuation Accuracy In Decibels:** -0.50 to 0.50 **Mounting Method:** Connector **Terminal Type And Quantity:** 2 connector Frequency Range: Between 0.000 hertz and 18.000 gigahertz Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No

NSN 5985-01-230-2977

Fixed Attenuator - Page 2 of 2



Fiig:

A20000