

View Online at <https://aerobasegroup.com/nsn/5985-01-230-4154>

Application Design:

Transmission line

Body Material:

Aluminum

Body Style:

Coaxial type

Overall Length:

1.920 inches

Overall Height:

1.420 inches

Overall Width:

1.000 inches

Shaft Diameter:

0.250 inches

Shaft Length:

1.920 inches

Operating Temperature Range:

-40.0 to 85.0 degrees celsius

End Application:

Projector, sonar tr-316/bqs

Voltage Standing Wave Ratio:

1.50

Coaxial Connector Series Designation:

Sma

Power Rating:

3.0 watts average

Mounting Facility Screw Thread Series Designator:

Unc

Insertion Loss At Minimum Attenuation In Maximum Decibels:

0.5

Overall Attenuation Range In Decibels:

+0.0 to 20.0

Attenuation Variation Method:

Stepped

Step Position Quantity:

10

Attenuation Per Step In Decibels:

2.0

Mounting Facility Type And Quantity:

4 threaded hole

Frequency Range:

Between 40.000 megahertz and 4.000 gigahertz

Overall Attenuation Accuracy In Decibels:

-1.00 to 1.00

Mounting Thread Quantity:

32 per inch

Adjustment Device Type And Quantity:

1 shaft and 1 slotted screw

Mounting Facility Pattern:

Four position diamond

Shaft Type:

Round, slotted

Mounting Facility Screw Thread Diameter:

0.138 inches

Terminal Type And Quantity:

2 connector, coaxial, female

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A223a0