## NSN 5985-01-231-3732

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-231-3732

Application Design:
Transmission line
Body Material:
Steel, corrosion resisting
Body Style:
Rectangular terminal/terminals on three surfaces
Body Surface Treatment:
Any acceptable
Overall Length:
1.080 inches
Overall Height:
0.687 inches
Overall Width:
0.687 inches
Voltage Standing Wave Ratio:
1.15
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
Sma
Power Rating:
1.0 watts average
Rf Signal Attenuation In Decibels:
19.5
Voltage Standing Wave Ratio Frequency Range:
+3.5 to 6.0 gigahertz
Attenuation Accuracy Reference Frequency:
6.0 gigahertz
Attenuation Accuracy In Decibels:
-0.50 to 0.50
Terminal Type And Quantity:
2 connector
Frequency Range:
Between 3.500 gigahertz and 6.000 gigahertz
Fsc Application Data:
Antennas, waveguides, and related equipment
Shelf Life:
N/a
Unit Of Measure:

--

## NSN 5985-01-231-3732

Fixed Attenuator - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A20000