

View Online at <https://aerobasegroup.com/nsn/5985-01-231-4254>

**Application Design:**

Transmission line

**Body Material:**

Steel, corrosion resisting

**Body Style:**

1b round, terminal/terminals in opposite surface

**Body Surface Treatment:**

Passivated

**Overall Length:**

0.750 inches

**Overall Diameter:**

0.361 inches

**Operating Temperature Range:**

-55.0 to 150.0 degrees celsius

**End Application:**

5865-00-209-3955 receiving set, countermeasures

**Voltage Standing Wave Ratio:**

1.10 and 1.15 and 1.30 and 1.70

**Input Impedance Rating In Ohms:**

50.0

**Output Impedance Rating In Ohms:**

50.0

**Coaxial Connector Series Designation:**

Sma

**Power Rating:**

1.0 watts average

**Rf Signal Attenuation In Decibels:**

4.0

**Voltage Standing Wave Ratio Frequency Range:**

+0.0 to 4.0 gigahertz and +4.0 to 8.0 gigahertz and +8.0 to 12.0 gigahertz and +12.0 to 18.0 gigahertz

**Attenuation Accuracy Reference Frequency:**

18.0 gigahertz

**Attenuation Accuracy In Decibels:**

-1.63 to 1.63

**Unpackaged Unit Weight:**

6.0 grams

**Mounting Method:**

Connector

**Terminal Type And Quantity:**

2 connector

**Frequency Range:**

Between 0.000 hertz and 18.000 gigahertz

**Precious Material And Location:**

Contact surfaces gold

**Precious Material:**

Gold

**Fsc Application Data:**

Antennas, waveguides, and related equipment

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A20000