NSN 5985-01-231-7056

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-231-7056

Application Design:					
Transmission line					
Body Material:					
Brass					
Body Style:					
1b round, terminal/terminals in opposite surface					
Overall Length:					
3.000 inches					
Overall Diameter:					
0.840 inches					
Operating Tempurature Range:					
-55.0 to 125.0 degrees celsius					
Voltage Standing Wave Ratio:					
1.15 and 1.20 and 1.25					
Input Impedance Rating In Ohms:					
50.0					
Output Impedance Rating In Ohms:					
50.0					
Coaxial Connector Series Designation:					
N					
Power Rating:					
5.0 watts average and 1.0 kilowatts peak					
Rf Signal Attenuation In Decibels:					
20.0					
Voltage Standing Wave Ratio Frequency Range:					
+0.0 to 4.0 gigahertz and +4.0 to 12.4 gigahertz and +12.4 to 18.0 gigahertz					
Attenuation Accuracy In Decibels:					
-0.50 to 0.50					
Frequency Sensitivity Attenuation In Decibels:					
0.50					
Connection Type Per Function:					
Female input and male output					
Unpackaged Unit Weight:					
0.100 kilograms					
Mounting Method:					
Connector					
Terminal Type And Quantity:					
2 connector					
Frequency Range:					
Between 0.000 hertz and 18.000 gigahertz					
Precious Material And Location:					

Contact surfaces gold

NSN 5985-01-231-7056

Fixed Attenuator - Page 2 of 2



P	reci	nus	Material	ŀ

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A20000