

View Online at <https://aerobasegroup.com/nsn/5985-01-231-8143>

**Application Design:**

Transmission line

**Body Material:**

Steel

**Body Style:**

1b round, terminal/terminals in opposite surface

**Terminal Material:**

Steel

**Terminal Surface Treatment:**

Passivated

**Body Surface Treatment:**

Passivated

**Overall Length:**

Between 1.190 inches and 1.290 inches

**Overall Diameter:**

0.390 inches

**Operating Temperature Range:**

-55.0 to 125.0 degrees celsius

**End Application:**

6920-01-119-7619 launcher group, guided missile

**Voltage Standing Wave Ratio:**

1.50 and 1.80

**Input Impedance Rating In Ohms:**

50.0

**Output Impedance Rating In Ohms:**

50.0

**Coaxial Connector Series Designation:**

Sma

**Power Rating:**

1.0 watts average

**Rf Signal Attenuation In Decibels:**

2.0

**Voltage Standing Wave Ratio Frequency Range:**

+0.0 to 12.4 gigahertz and +12.4 to 18.0 gigahertz

**Attenuation Accuracy In Decibels:**

-0.50 to 0.50

**Mounting Method:**

Connector

**Terminal Type And Quantity:**

2 connector

**Frequency Range:**

Between 0.000 hertz and 18.000 gigahertz

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A20000