NSN 5985-01-232-0560



Fixed Attenuator - Page 1 of 2
View Online at https://aerobasegroup.com/nsn/5985-01-232-0560
Application Design:
Transmission line
Body Material:
Steel, stainless
Body Style:
1b round, terminal/terminals in opposite surface
Body Surface Treatment:
Any acceptable
Overall Length:
1.140 inches
Overall Diameter:
0.340 inches
Voltage Standing Wave Ratio:
1.25
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
Sma
Power Rating:
1.0 watts average and 1.0 kilowatts peak
Rf Signal Attenuation In Decibels:
10.0
Voltage Standing Wave Ratio Frequency Range:
+0.0 to 5.0 gigahertz
Attenuation Accuracy Reference Frequency:
5.0 gigahertz
Attenuation Accuracy In Decibels:
-0.60 to 0.60
Connection Type Per Function:
Female input and male output
Mounting Method:

Connector

Terminal Type And Quantity:

2 connector

Frequency Range:

Between 0.000 hertz and 5.000 gigahertz

Fsc Application Data:

Antennas, waveguides, and related equipment

Shelf Life:

N/a

NSN 5985-01-232-0560

Fixed Attenuator - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A20000