NSN 5985-01-232-2120

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-232-2120

Application Design:
Transmission line
Body Material:
Aluminum alloy
Body Style:
Coaxial type
Overall Length:
4.250 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
Between 1.240 inches and 1.260 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
Between 1.802 inches and 1.822 inches
Overall Height:
3.800 inches
Overall Width:
Between 0.960 inches and 1.030 inches
Voltage Standing Wave Ratio:
1.40
Coaxial Connector Series Designation:
N
Power Rating:
4.0 watts average
Mounting Facility Screw Thread Series Designator:
Unc
Insertion Loss At Minimum Attenuation In Maximum Decibels:
0.6
Overall Attenuation Range In Decibels:
+0.0/+10.0
Attenuation Variation Method:
Continuous
Mounting Facility Type And Quantity:
4 threaded hole
Mounting Thread Quantity:
32 per inch
Adjustment Device Type And Quantity:
1 slotted screw
Mounting Facility Pottorn.
Mounting Facility Pattern:
Four position rectangular
Four position rectangular

50.0 input-output

NSN 5985-01-232-2120

Variable Attenuator - Page 2 of 2



Terminal Type And Quantity	[erminal	Type	And	Quantity	/ :
----------------------------	----------	-------------	-----	----------	------------

2 connector, coaxial, female

Fsc Application Data:

Antennas, waveguides, and related equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A223a0