NSN 5985-01-232-5776

Fixed Attenuator - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5985-01-232-5776



Application Design: Transmission line **Body Material:** Steel, stainless **Body Style:** 1b round, terminal/terminals in opposite surface **Body Surface Treatment:** Passivated **Overall Length:** Between 1.000 inches and 1.040 inches **Overall Diameter:** Between 0.278 inches and 0.282 inches **Operating Tempurature Range:** -55.0 to 85.0 degrees celsius **End Application:** Adv memory sys alq-117 **Voltage Standing Wave Ratio:** 1.15 and 1.23 and 1.27 and 1.35 Input Impedance Rating In Ohms: 50.0 **Output Impedance Rating In Ohms:** 50.0 **Coaxial Connector Series Designation:** Sma **Rf Signal Attenuation In Decibels:** 15.0 Voltage Standing Wave Ratio Frequency Range: +0.0 to 4.0 gigahertz and +4.0 to 8.0 gigahertz and +8.0 to 12.4 gigahertz and +12.4 to 18.0 gigahertz **Attenuation Accuracy Reference Frequency:** 18.0 gigahertz **Attenuation Accuracy In Decibels:** -0.50 to 0.50 **Connection Type Per Function:** Female input and male output **Unpackaged Unit Weight:** 0.175 ounces **Mounting Method:** Connector **Terminal Type And Quantity:** 2 connector **Frequency Range:** Between 0.000 hertz and 18.000 gigahertz

NSN 5985-01-232-5776

Fixed Attenuator - Page 2 of 2



Precious Material And Location:

Contact surfaces gold

Precious Material:

Gold

Fsc Application Data:

Antennas, waveguides, and related equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A20000