NSN 5985-01-233-9421

Variable Attenuator - Page 1 of 1

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5985-01-233-9421

View Online at https://aerobasegroup.com/nsn/5985-01-233-9421
Application Design:
Transmission line
Body Material:
Steel
Body Style:
Coaxial type
Overall Height:
1.890 inches
Overall Width:
0.900 inches
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
End Application:
5840-01-192-7572 transmitter, radar
Voltage Standing Wave Ratio:
1.30
Power Rating:
10.0 watts average and 5.0 watts peak
Insertion Loss At Minimum Attenuation In Maximum Decibels:
0.4
Overall Attenuation Range In Decibels:
Overall Attenuation Range In Decibels: +0.0/+30.0
-
+0.0/+30.0
+0.0/+30.0 Attenuation Variation Method:
+0.0/+30.0 Attenuation Variation Method: Continuous
+0.0/+30.0 Attenuation Variation Method: Continuous Frequency Range:
+0.0/+30.0 Attenuation Variation Method: Continuous Frequency Range: Between 4.000 gigahertz and 8.000 gigahertz
+0.0/+30.0 Attenuation Variation Method: Continuous Frequency Range: Between 4.000 gigahertz and 8.000 gigahertz Adjustment Device Type And Quantity:
+0.0/+30.0 Attenuation Variation Method: Continuous Frequency Range: Between 4.000 gigahertz and 8.000 gigahertz Adjustment Device Type And Quantity: 1 slotted screw
+0.0/+30.0 Attenuation Variation Method: Continuous Frequency Range: Between 4.000 gigahertz and 8.000 gigahertz Adjustment Device Type And Quantity: 1 slotted screw Shaft Type:
+0.0/+30.0 Attenuation Variation Method: Continuous Frequency Range: Between 4.000 gigahertz and 8.000 gigahertz Adjustment Device Type And Quantity: 1 slotted screw Shaft Type: Round, slotted
+0.0/+30.0 Attenuation Variation Method: Continuous Frequency Range: Between 4.000 gigahertz and 8.000 gigahertz Adjustment Device Type And Quantity: 1 slotted screw Shaft Type: Round, slotted Shelf Life:
+0.0/+30.0 Attenuation Variation Method: Continuous Frequency Range: Between 4.000 gigahertz and 8.000 gigahertz Adjustment Device Type And Quantity: 1 slotted screw Shaft Type: Round, slotted Shelf Life: N/a
+0.0/+30.0 Attenuation Variation Method: Continuous Frequency Range: Between 4.000 gigahertz and 8.000 gigahertz Adjustment Device Type And Quantity: 1 slotted screw Shaft Type: Round, slotted Shelf Life: N/a Unit Of Measure:
+0.0/+30.0 Attenuation Variation Method: Continuous Frequency Range: Between 4.000 gigahertz and 8.000 gigahertz Adjustment Device Type And Quantity: 1 slotted screw Shaft Type: Round, slotted Shelf Life: N/a Unit Of Measure:
+0.0/+30.0 Attenuation Variation Method: Continuous Frequency Range: Between 4.000 gigahertz and 8.000 gigahertz Adjustment Device Type And Quantity: 1 slotted screw Shaft Type: Round, slotted Shelf Life: N/a Unit Of Measure:
+0.0/+30.0 Attenuation Variation Method: Continuous Frequency Range: Between 4.000 gigahertz and 8.000 gigahertz Adjustment Device Type And Quantity: 1 slotted screw Shaft Type: Round, slotted Shelf Life: N/a Unit Of Measure: Demilitarization: No
+0.0/+30.0 Attenuation Variation Method: Continuous Frequency Range: Between 4.000 gigahertz and 8.000 gigahertz Adjustment Device Type And Quantity: 1 slotted screw Shaft Type: Round, slotted Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: