# NSN 5985-01-234-0603

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-234-0603

### **Cross Sectional Shape:**

Internal, rectangular double ridged external, rectangular

**End Application:** 

An/alq-172v2

**Tubing Wall Construction Style:** 

Seamless single tubing segment

Flange Quantity:

2

#### Flange Inside Width:

0.720 inches all flanges

#### Flange Inside Height:

0.321 inches all flanges

Flange Outside Width:

1.375 inches all flanges

Flange Outside Height:

1.375 inches all flanges

#### Flange Depth:

0.250 inches all flanges

## Flange Connecting Hole Diameter:

0.147 inches all flanges all connection facilities and 0.147 inches all flanges all connection facilities

# Voltage Standing Wave Ratio:

1.40

Insertion Loss In Decibels:

0.30

#### Waveguide Outside Width:

0.730 inches

#### Waveguide Inside Width:

0.720 inches

## Waveguide Inside Height:

0.321 inches

### Waveguide Outside Height:

0.421 inches

#### Flange Connecting Facility And Quantity:

4 unthreaded hole all flanges all connection facilities

### Flange Style:

Contact, double ridge type all flanges

### Waveguide Length:

10.500 inches

Flexibility:

Flexible single tubing segment

#### Material:

Copper alloy single tubing segment

# NSN 5985-01-234-0603

Waveguide Assembly - Page 2 of 2



## Surface Treatment:

Any acceptable all tubing segment and flange outside surfaces

## Style Designator:

Straight type

## **Fsc Application Data:**

Antennas, waveguides, and related equipment

Shelf Life:

N/a

Unit Of Measure:

--

# Demilitarization:

Yes - demil/mli

Fiig:

A073a0