NSN 5985-01-234-0603

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-234-0603
Cross Sectional Shape:
Internal, rectangular double ridged external, rectangular
End Application:
An/alq-172v2
Tubing Wall Construction Style:
Seamless single tubing segment
Flange Quantity:
2
Flange Inside Width:
0.720 inches all flanges
Flange Inside Height:
0.321 inches all flanges
Flange Outside Width:
1.375 inches all flanges
Flange Outside Height:
1.375 inches all flanges
Flange Depth:
0.250 inches all flanges
Flange Connecting Hole Diameter:
0.147 inches all flanges all connection facilities and 0.147 inches all flanges all connection facilities
Voltage Standing Wave Ratio:
1.40
Insertion Loss In Decibels:
0.30
Waveguide Outside Width:
0.730 inches
Waveguide Inside Width:
0.720 inches
Waveguide Inside Height:
0.321 inches
Waveguide Outside Height:
0.421 inches
Flange Connecting Facility And Quantity:
4 unthreaded hole all flanges all connection facilities
Flange Style:
Contact double ridge type all flanges

Contact, double ridge type all flanges

Waveguide Length:

10.500 inches

Flexibility:

Flexible single tubing segment

Material:

Copper alloy single tubing segment

NSN 5985-01-234-0603

Waveguide Assembly - Page 2 of 2



_		_				
S	rface	.	00	tm.	an	٠.
Ju	Hate	7 II	Cai			L.

Any acceptable all tubing segment and flange outside surfaces

Style Designator:

Straight type

Fsc Application Data:

Antennas, waveguides, and related equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A073a0