NSN 5985-01-234-2342

Fixed Attenuator - Page 1 of 2

Application Design:



View Online at https://aerobasegroup.com/nsn/5985-01-234-2342

Transmission line		
Body Material:		
Steel, stainless		
Body Style:		
Round, terminal/terminals in opposite surface		
Terminal Material:		
Beryllium copper		
Terminal Surface Treatment:		
Gold plated		
Body Surface Treatment:		
Passivated		
Overall Length:		
1.120 inches		
Overall Diameter:		
0.312 inches		
Voltage Standing Wave Ratio:		
1.07		
Input Impedance Rating In Ohms:		
50.0		
Output Impedance Rating In Ohms:		
50.0		
Coaxial Connector Series Designation:		
Bnc		
Power Rating:		
Power Rating:		
Power Rating: 2.0 watts average		
Power Rating: 2.0 watts average Rf Signal Attenuation In Decibels:		
Power Rating: 2.0 watts average Rf Signal Attenuation In Decibels: 15.0		
Power Rating: 2.0 watts average Rf Signal Attenuation In Decibels: 15.0 Attenuation Accuracy In Decibels:		
Power Rating: 2.0 watts average Rf Signal Attenuation In Decibels: 15.0 Attenuation Accuracy In Decibels: -1.00/+1.00		
Power Rating: 2.0 watts average Rf Signal Attenuation In Decibels: 15.0 Attenuation Accuracy In Decibels: -1.00/+1.00 Connection Type Per Function:		
Power Rating: 2.0 watts average Rf Signal Attenuation In Decibels: 15.0 Attenuation Accuracy In Decibels: -1.00/+1.00 Connection Type Per Function: Male input and male output		
Power Rating: 2.0 watts average Rf Signal Attenuation In Decibels: 15.0 Attenuation Accuracy In Decibels: -1.00/+1.00 Connection Type Per Function: Male input and male output Mounting Method:		
Power Rating: 2.0 watts average Rf Signal Attenuation In Decibels: 15.0 Attenuation Accuracy In Decibels: -1.00/+1.00 Connection Type Per Function: Male input and male output Mounting Method: Connector		
Power Rating: 2.0 watts average Rf Signal Attenuation In Decibels: 15.0 Attenuation Accuracy In Decibels: -1.00/+1.00 Connection Type Per Function: Male input and male output Mounting Method: Connector Terminal Type And Quantity:		
Power Rating: 2.0 watts average Rf Signal Attenuation In Decibels: 15.0 Attenuation Accuracy In Decibels: -1.00/+1.00 Connection Type Per Function: Male input and male output Mounting Method: Connector Terminal Type And Quantity: 2 connector		
Power Rating: 2.0 watts average Rf Signal Attenuation In Decibels: 15.0 Attenuation Accuracy In Decibels: -1.00/+1.00 Connection Type Per Function: Male input and male output Mounting Method: Connector Terminal Type And Quantity: 2 connector Frequency Range:		
Power Rating: 2.0 watts average Rf Signal Attenuation In Decibels: 15.0 Attenuation Accuracy In Decibels: -1.00/+1.00 Connection Type Per Function: Male input and male output Mounting Method: Connector Terminal Type And Quantity: 2 connector Frequency Range: Between 0.000 gigahertz and 18.000 gigahertz		
Power Rating: 2.0 watts average Rf Signal Attenuation In Decibels: 15.0 Attenuation Accuracy In Decibels: -1.00/+1.00 Connection Type Per Function: Male input and male output Mounting Method: Connector Terminal Type And Quantity: 2 connector Frequency Range: Between 0.000 gigahertz and 18.000 gigahertz Precious Material And Location:		

NSN 5985-01-234-2342

Fixed Attenuator - Page 2 of 2



	Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A20000