# NSN 5985-01-234-3326

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-234-3326

# Application Design:

Transmission line

## Body Style:

Irregular

## Overall Length:

2.960 inches

## Center To Center Distance Between Mounting Facilities Parallel To Length:

1.500 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.689 inches

### **Overall Height:**

0.460 inches

## Overall Width:

2.340 inches

## Shaft Diameter:

0.500 inches

## Shaft Length:

0.590 inches

#### Center To Center Distance Between Mounting Facilities Parallel To Height:

0.875 inches

#### **End Application:**

Training set, tactical electronic warfare an/msq-t13

#### Voltage Standing Wave Ratio:

1.50

#### **Coaxial Connector Series Designation:**

Sma

#### **Power Rating:**

0.5 watts average

#### Mounting Facility Screw Thread Series Designator:

Unc

# Insertion Loss At Minimum Attenuation In Maximum Decibels:

2.1

# **Overall Attenuation Range In Decibels:**

+0.0/+25.0

# Attenuation Variation Method:

Continuous

# Mounting Facility Type And Quantity:

8 threaded hole

### Frequency Range:

Between 0.000 megahertz and 200.000 gigahertz

# **Overall Attenuation Accuracy In Decibels:**

-0.25/+0.25

# NSN 5985-01-234-3326

Variable Attenuator - Page 2 of 2



Mounting Thread Quantity:

40 per inch

Adjustment Device Type And Quantity:

1 shaft

Mounting Facility Pattern:

Four position rectangular

Shaft Type:

Round, slotted

Mounting Facility Screw Thread Diameter:

0.112 inches

Terminal Type And Quantity:

2 connector, coaxial, female

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A223a0