NSN 5985-01-234-3326

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-234-3326

Application Design:
Transmission line
Body Style:
Irregular
Overall Length:
2.960 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.500 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
0.689 inches
Overall Height:
0.460 inches
Overall Width:
2.340 inches
Shaft Diameter:
0.500 inches
Shaft Length:
0.590 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.875 inches
End Application:
Training set, tactical electronic warfare an/msq-t13
Voltage Standing Wave Ratio:
1.50
Coaxial Connector Series Designation:
Sma
Power Rating:
0.5 watts average
Mounting Facility Screw Thread Series Designator:
Unc
Insertion Loss At Minimum Attenuation In Maximum Decibels:
2.1
Overall Attenuation Range In Decibels:
+0.0/+25.0
Attenuation Variation Method:
Continuous
Mounting Facility Type And Quantity:
8 threaded hole
Frequency Range:
Between 0.000 megahertz and 200.000 gigahertz
Overall Attenuation Accuracy In Decibels:

-0.25/+0.25

NSN 5985-01-234-3326

Variable Attenuator - Page 2 of 2



Mounting Thread Quantity:
40 per inch
Adjustment Device Type And Quantity:
1 shaft
Mounting Facility Pattern:
Four position rectangular
Shaft Type:
Round, slotted
Mounting Facility Screw Thread Diameter:
0.112 inches
Terminal Type And Quantity:
2 connector, coaxial, female
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A223a0