## NSN 5985-01-235-6823

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-235-6823

Application Design:
Transmission line
Body Material:
Steel, stainless
Body Style:
Err-090
Body Surface Treatment:
Passivated
Overall Length:
1.200 inches
Overall Diameter:
0.360 inches
Operating Tempurature Range:
-65.0/+125.0 degrees celsius
Voltage Standing Wave Ratio:
1.14 and 1.23 and 1.27 and 1.35
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
Sma
Power Rating:
2.0 watts average
Rf Signal Attenuation In Decibels:
10.0
Voltage Standing Wave Ratio Frequency Range:
+0.0/+4.0 gigahertz and +4.0/+10.0 gigahertz and +10.0/+12.4 gigahertz and +12.4/+18.0 gigahertz
Attenuation Accuracy Reference Frequency:
18.0 gigahertz
Attenuation Accuracy In Decibels:
-0.30/+0.30
Temperature Sensitivity Attenuation In Decibels:
0.0010
Mounting Method:
Connector
Terminal Type And Quantity:
2 connector
Frequency Range:
Between 0.000 hertz and 18.000 gigahertz
Fsc Application Data:

1 30 Application Data:

Antennas, waveguides, and related equipment

## NSN 5985-01-235-6823

Fixed Attenuator - Page 2 of 2



Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A20000