NSN 5985-01-237-4009

Fixed Attenuator - Page 1 of 2

Application Design: Transmission line



View Online at https://aerobasegroup.com/nsn/5985-01-237-4009

Body Material:
Steel, stainless
Body Style:
Err-090
Body Surface Treatment:
Passivated
Overall Length:
Between 0.840 inches and 0.880 inches
Overall Diameter:
0.280 inches
Operating Tempurature Range:
-28.0/+90.0 degrees celsius
End Application:
Countermeasures set an/slq-3 (v)
Voltage Standing Wave Ratio:
1.15 and 1.20
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
Sma
Sma Power Rating:
Power Rating:
Power Rating: 2.0 watts average
Power Rating: 2.0 watts average Rf Signal Attenuation In Decibels:
Power Rating: 2.0 watts average Rf Signal Attenuation In Decibels: 12.0
Power Rating: 2.0 watts average Rf Signal Attenuation In Decibels: 12.0 Voltage Standing Wave Ratio Frequency Range:
Power Rating: 2.0 watts average Rf Signal Attenuation In Decibels: 12.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+4.0 gigahertz and +4.0/+8.0 gigahertz
Power Rating: 2.0 watts average Rf Signal Attenuation In Decibels: 12.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+4.0 gigahertz and +4.0/+8.0 gigahertz Attenuation Accuracy In Decibels:
Power Rating: 2.0 watts average Rf Signal Attenuation In Decibels: 12.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+4.0 gigahertz and +4.0/+8.0 gigahertz Attenuation Accuracy In Decibels: -0.50/+0.50
Power Rating: 2.0 watts average Rf Signal Attenuation In Decibels: 12.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+4.0 gigahertz and +4.0/+8.0 gigahertz Attenuation Accuracy In Decibels: -0.50/+0.50 Mounting Method:
Power Rating: 2.0 watts average Rf Signal Attenuation In Decibels: 12.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+4.0 gigahertz and +4.0/+8.0 gigahertz Attenuation Accuracy In Decibels: -0.50/+0.50 Mounting Method: Connector
Power Rating: 2.0 watts average Rf Signal Attenuation In Decibels: 12.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+4.0 gigahertz and +4.0/+8.0 gigahertz Attenuation Accuracy In Decibels: -0.50/+0.50 Mounting Method: Connector Terminal Type And Quantity:
Power Rating: 2.0 watts average Rf Signal Attenuation In Decibels: 12.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+4.0 gigahertz and +4.0/+8.0 gigahertz Attenuation Accuracy In Decibels: -0.50/+0.50 Mounting Method: Connector Terminal Type And Quantity: 2 connector
Power Rating: 2.0 watts average Rf Signal Attenuation In Decibels: 12.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+4.0 gigahertz and +4.0/+8.0 gigahertz Attenuation Accuracy In Decibels: -0.50/+0.50 Mounting Method: Connector Terminal Type And Quantity: 2 connector Frequency Range:
Power Rating: 2.0 watts average Rf Signal Attenuation In Decibels: 12.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+4.0 gigahertz and +4.0/+8.0 gigahertz Attenuation Accuracy In Decibels: -0.50/+0.50 Mounting Method: Connector Terminal Type And Quantity: 2 connector Frequency Range: Between 0.000 hertz and 8.000 gigahertz
Power Rating: 2.0 watts average Rf Signal Attenuation In Decibels: 12.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+4.0 gigahertz and +4.0/+8.0 gigahertz Attenuation Accuracy In Decibels: -0.50/+0.50 Mounting Method: Connector Terminal Type And Quantity: 2 connector Frequency Range: Between 0.000 hertz and 8.000 gigahertz Shelf Life:

NSN 5985-01-237-4009

Fixed Attenuator - Page 2 of 2



Demilitarization:

No

Fiig:

A20000