## NSN 5985-01-237-4009

Fixed Attenuator - Page 1 of 2

**Application Design:** Transmission line



View Online at https://aerobasegroup.com/nsn/5985-01-237-4009

Body Material:
Steel, stainless
Body Style:
Err-090
<b>Body Surface Treatment:</b>
Passivated
Overall Length:
Between 0.840 inches and 0.880 inches
Overall Diameter:
0.280 inches
Operating Tempurature Range:
-28.0/+90.0 degrees celsius
End Application:
Countermeasures set an/slq-3 (v)
Voltage Standing Wave Ratio:
1.15 and 1.20
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
Sma
Sma Power Rating:
Power Rating:
Power Rating: 2.0 watts average
Power Rating: 2.0 watts average  Rf Signal Attenuation In Decibels:
Power Rating: 2.0 watts average  Rf Signal Attenuation In Decibels: 12.0
Power Rating: 2.0 watts average  Rf Signal Attenuation In Decibels: 12.0  Voltage Standing Wave Ratio Frequency Range:
Power Rating: 2.0 watts average  Rf Signal Attenuation In Decibels: 12.0  Voltage Standing Wave Ratio Frequency Range: +0.0/+4.0 gigahertz and +4.0/+8.0 gigahertz
Power Rating:  2.0 watts average  Rf Signal Attenuation In Decibels:  12.0  Voltage Standing Wave Ratio Frequency Range: +0.0/+4.0 gigahertz and +4.0/+8.0 gigahertz  Attenuation Accuracy In Decibels:
Power Rating:  2.0 watts average  Rf Signal Attenuation In Decibels:  12.0  Voltage Standing Wave Ratio Frequency Range: +0.0/+4.0 gigahertz and +4.0/+8.0 gigahertz  Attenuation Accuracy In Decibels: -0.50/+0.50
Power Rating:  2.0 watts average  Rf Signal Attenuation In Decibels:  12.0  Voltage Standing Wave Ratio Frequency Range: +0.0/+4.0 gigahertz and +4.0/+8.0 gigahertz  Attenuation Accuracy In Decibels: -0.50/+0.50  Mounting Method:
Power Rating:  2.0 watts average  Rf Signal Attenuation In Decibels:  12.0  Voltage Standing Wave Ratio Frequency Range: +0.0/+4.0 gigahertz and +4.0/+8.0 gigahertz  Attenuation Accuracy In Decibels: -0.50/+0.50  Mounting Method:  Connector
Power Rating:  2.0 watts average  Rf Signal Attenuation In Decibels:  12.0  Voltage Standing Wave Ratio Frequency Range: +0.0/+4.0 gigahertz and +4.0/+8.0 gigahertz  Attenuation Accuracy In Decibels: -0.50/+0.50  Mounting Method:  Connector  Terminal Type And Quantity:
Power Rating:  2.0 watts average  Rf Signal Attenuation In Decibels:  12.0  Voltage Standing Wave Ratio Frequency Range: +0.0/+4.0 gigahertz and +4.0/+8.0 gigahertz  Attenuation Accuracy In Decibels: -0.50/+0.50  Mounting Method:  Connector  Terminal Type And Quantity: 2 connector
Power Rating:  2.0 watts average  Rf Signal Attenuation In Decibels:  12.0  Voltage Standing Wave Ratio Frequency Range: +0.0/+4.0 gigahertz and +4.0/+8.0 gigahertz  Attenuation Accuracy In Decibels: -0.50/+0.50  Mounting Method:  Connector  Terminal Type And Quantity: 2 connector  Frequency Range:
Power Rating:  2.0 watts average  Rf Signal Attenuation In Decibels:  12.0  Voltage Standing Wave Ratio Frequency Range: +0.0/+4.0 gigahertz and +4.0/+8.0 gigahertz  Attenuation Accuracy In Decibels: -0.50/+0.50  Mounting Method:  Connector  Terminal Type And Quantity: 2 connector  Frequency Range:  Between 0.000 hertz and 8.000 gigahertz
Power Rating:  2.0 watts average  Rf Signal Attenuation In Decibels:  12.0  Voltage Standing Wave Ratio Frequency Range: +0.0/+4.0 gigahertz and +4.0/+8.0 gigahertz  Attenuation Accuracy In Decibels: -0.50/+0.50  Mounting Method: Connector  Terminal Type And Quantity: 2 connector  Frequency Range: Between 0.000 hertz and 8.000 gigahertz  Shelf Life:

## NSN 5985-01-237-4009

Fixed Attenuator - Page 2 of 2



Demilitarization:

No

Fiig:

A20000