## NSN 5985-01-237-4011

Fixed Attenuator - Page 1 of 2

**Application Design:** 



View Online at https://aerobasegroup.com/nsn/5985-01-237-4011

Transmission line
Body Material:
Steel, stainless
Body Style:
Err-090
<b>Body Surface Treatment:</b>
Passivated
Overall Length:
Between 0.840 inches and 0.880 inches
Overall Diameter:
0.280 inches
Operating Tempurature Range:
-28.0/+90.0 degrees celsius
End Application:
Countermeasures set an/slq-3 (v)
Voltage Standing Wave Ratio:
1.15 and 1.20
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
Sma
Power Rating:
2.0 watts average
Rf Signal Attenuation In Decibels:
10.0
Voltage Standing Wave Ratio Frequency Range:
+0.0/+4.0 gigahertz and +4.0/+8.0 gigahertz
Attenuation Accuracy In Decibels:
-0.50/+0.50
Mounting Method:
Connector
Terminal Type And Quantity:
2 connector
Frequency Range:
Between 0.000 hertz and 8.000 gigahertz
Shelf Life:
N/a
Unit Of Measure:

## NSN 5985-01-237-4011

Fixed Attenuator - Page 2 of 2



Demilitarization:

No

Fiig:

A20000