## NSN 5985-01-237-5342

Fixed Attenuator - Page 1 of 2

**Application Design:** 



View Online at https://aerobasegroup.com/nsn/5985-01-237-5342

Transmission line			
Body Material:			
Steel, stainless			
Body Style:			
Err-090			
Body Surface Treatment:			
Passivated			
Overall Length:			
0.930 inches			
Overall Diameter:			
0.385 inches			
Voltage Standing Wave Ratio:			
1.20			
Input Impedance Rating In Ohms:			
50.0			
Output Impedance Rating In Ohms:			
50.0			
Coaxial Connector Series Designation:			
Sma			
Power Rating:			
2.0 watts average and 0.2 kilowatts peak			
Rf Signal Attenuation In Decibels:			
20.0			
Voltage Standing Wave Ratio Frequency Range:			
+0.0/+6.0 gigahertz			
Attenuation Accuracy Reference Frequency:			
6.0 gigahertz			
Attenuation Accuracy In Decibels:			
-0.50/+0.50			
Connection Type Per Function:			
Female input and male output			
Unpackaged Unit Weight:			
0.500 ounces			
Mounting Method:			
Connector			
Terminal Type And Quantity:			
2 connector			
Frequency Range:			
Between 0.000 hertz and 6.000 gigahertz			
Fsc Application Data:			
Antennas waveguides and related equipment			

## NSN 5985-01-237-5342

Fixed Attenuator - Page 2 of 2



She	lf	I if	ρ.
~	•••		•

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A20000