NSN 5985-01-237-5343

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-237-5343

ŀ	Application Design:
Т	Fransmission line
E	Body Material:
E	Brass
E	Body Style:
E	Err-090
E	Body Surface Treatment:
٢	Nickel plated
(Overall Length:
1	.700 inches
C	Overall Diameter:
С	0.430 inches
E	End Application:
	Radio set an/frc-39
١	/oltage Standing Wave Ratio:
1	.30 and 1.50 and 1.70
h	nput Impedance Rating In Ohms:
5	50.0
(Dutput Impedance Rating In Ohms:
5	50.0
(Coaxial Connector Series Designation:
S	Sma
F	Rf Signal Attenuation In Decibels:
6	8.0
١	/oltage Standing Wave Ratio Frequency Range:
+	+0.0/+0.5 gigahertz and +0.5/+1.0 gigahertz and +1.0/+1.5 gigahertz
ŀ	Attenuation Accuracy Reference Frequency:
1	.5 gigahertz
ŀ	Attenuation Accuracy In Decibels:
-	0.30/+0.30
(Connection Type Per Function:
F	Female input and male output
N	Nounting Method:
C	Connector
٦	Ferminal Type And Quantity:
2	2 connector
F	Frequency Range:
E	Between 0.000 hertz and 1.500 gigahertz
F	-sc Application Data:
A	Antennas, waveguides and related equip.
S	Shelf Life:

NSN 5985-01-237-5343

Fixed Attenuator - Page 2 of 2

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A20000

