NSN 5985-01-238-0530



Fixed Attenuator - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5985-01-238-0530 **Body Material:** Copper alloy **Body Style:** Rectangular terminal/terminals on three surfaces **Body Surface Treatment:** Nickel plated **Overall Length:** 0.624 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 0.340 inches **Overall Height:** 0.500 inches **Overall Width:** 0.500 inches **Mounting Hole/stud Quantity: Unthreaded Mounting Hole Diameter:** 0.104 inches **Operating Tempurature Range:** -55.0/+100.0 degrees celsius **Voltage Standing Wave Ratio:** 1.20 **Input Impedance Rating In Ohms:** 50.0 **Output Impedance Rating In Ohms:** 50.0 **Power Rating:** 15.0 watts average **Voltage Standing Wave Ratio Frequency Range:** +4.0/+8.0 gigahertz **Connection Type Per Function:** Male input **Mounting Method:** Flange w/mounting hole **Terminal Type And Quantity:** 1 pin Frequency Range: Between 0.000 hertz and 12.400 gigahertz

Precious Material And Location:

Center contact surfaces gold

Precious Material:

Gold

NSN 5985-01-238-0530

Fixed Attenuator - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A20000