## NSN 5985-01-238-2359

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-238-2359

Application Design:
Transmission line
Body Material:
Silver
Body Style:
Err-090
Terminal Material:
Steel, stainless
Terminal Surface Treatment:
Passivated
Overall Length:
3.310 inches
Overall Diameter:
0.560 inches
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Voltage Standing Wave Ratio:
1.25
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
Sma
Power Rating:
5.0 watts average and 3.0 kilowatts peak
Rf Signal Attenuation In Decibels:
50.0
Voltage Standing Wave Ratio Frequency Range:
+0.0/+4.0 gigahertz
Attenuation Accuracy Reference Frequency:
4.0 gigahertz
Attenuation Accuracy In Decibels:
-1.50/+1.50
Connection Type Per Function:
Female output and male input
Mounting Method:
Connector
Terminal Type And Quantity:
2 connector
Frequency Range:
Between 0 000 hertz and 4 000 gigahertz

## **NSN 5985-01-238-2359** Fixed Attenuator - Page 2 of 2



Precious Material And Location:
Body silver
Precious Material:
Silver
Fsc Application Data:
Antennas, waveguides, and related equipment
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli

Fiig: A20000