

View Online at <https://aerobasegroup.com/nsn/5985-01-239-4946>

**Application Design:**

Transmission line

**Body Material:**

Tellurium copper and beryllium copper, qq-c-533, cond a

**Body Style:**

Rectangular terminal/terminals on opposite surfaces

**Body Surface Treatment:**

Gold plate over copper and silver plated, qq-s-365

**Overall Length:**

0.750 inches

**Overall Height:**

0.140 inches

**Overall Width:**

0.250 inches

**Operating Temperature Range:**

-55.0/+150.0 degrees celsius

**Voltage Standing Wave Ratio:**

1.25 and 1.50

**Input Impedance Rating In Ohms:**

50.0

**Output Impedance Rating In Ohms:**

50.0

**Power Rating:**

1.0 watts average

**Rf Signal Attenuation In Decibels:**

6.0

**Voltage Standing Wave Ratio Frequency Range:**

+0.0/+4.0 gigahertz and +8.0/+12.0 gigahertz

**Terminal Type And Quantity:**

2 tab, solder lug

**Frequency Range:**

Between 0.000 hertz and 12.000 gigahertz

**Precious Material And Location:**

Housing gold and tab surfaces silver

**Precious Material:**

Gold and silver

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A20000