NSN 5985-01-240-4304

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-240-4304

Annlingtion Design.
Application Design: Transmission line
Body Style:
Overall Length: 5.750 inches
Center To Center Distance Between Mounting Facilities Parallel To Length: 5.375 inches
Center To Center Distance Between Mounting Facilities Parallel To Width: 1.250 inches
Overall Height:
Overall Width:
1.750 inches
Unthreaded Mounting Hole Diameter: 0.144 inches
Voltage Standing Wave Ratio: 1.25
Coaxial Connector Series Designation:
Sma
Insertion Loss At Minimum Attenuation In Maximum Decibels:
3.5
Overall Attenuation Range In Decibels:
+0.0/+63.0
Attenuation Variation Method:
Stepped
Step Position Quantity:
7
/ Mounting Facility Type And Quantity:
4 unthreaded hole
Frequency Range:
Between 0.000 hertz and 400.000 megahertz
Adjustment Device Type And Quantity:
7 solenoid
Mounting Facility Pattern:
Four position rectangular
Impedance Rating In Ohms:
50.0 input-output
Terminal Type And Quantity:
2 connector, coaxial, female and 8 tab, solder lug
Shelf Life:

N/a

NSN 5985-01-240-4304

Variable Attenuator - Page 2 of 2

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A223a0

