

View Online at <https://aerobasegroup.com/nsn/5985-01-241-6993>

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b first flange all connection facilities

Thread Direction:

Right-hand first flange all connection facilities

Tubing Wall Construction Style:

Seamless single tubing segment

Tubing Twist Type:

Twistable single tubing segment

Tubing Twist Angle In Deg:

95.0 single tubing segment

Flange Quantity:

2

Flange Inside Width:

1.003 inches second flange

Flange Inside Height:

0.505 inches second flange

Flange Outside Width:

1.625 inches second flange

Flange Outside Height:

1.625 inches first flange

Flange Inside Diameter:

0.909 inches first flange

Flange Depth:

0.438 inches second flange

Flange Connecting Hole Diameter:

0.169 inches second flange all connection facilities

Voltage Standing Wave Ratio:

1.15

Thready Qty Per Inch (tpi):

32 first flange all connection facilities

Maximum Operating Pressure:

30.0 pounds per square inch gage

Waveguide Outside Width:

1.000 inches

Thread Size:

0.164 inches first flange all connection facilities

Waveguide Inside Width:

0.900 inches

Waveguide Inside Height:

0.400 inches

Waveguide Outside Height:

0.500 inches

Flange Connecting Facility And Quantity:

4 unthreaded hole second flange all connection facilities

Flange Style:

Cover type second flange

Waveguide Length:

26.000 inches

Flexibility:

Flexible single tubing segment

Material:

Copper alloy all flange

Surface Treatment:

Any acceptable all flange all surfaces

Style Designator:

Straight type

Thread Series Designator:

Unc first flange all connection facilities

Specification Data:

81349-mil-w-287/3 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A073a0