## NSN 5985-01-243-0838

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-243-0838

## **Cross Sectional Shape:**

Internal, rectangular external, rectangular

**Thread Class:** 

2b all flanges all connection facilities

**Thread Direction:** 

Right-hand all flanges all connection facilities

**Tubing Wall Construction Style:** 

Seamless single tubing segment

**Tubing Twist Type:** 

Twistable single tubing segment

Flange Quantity:

2

Flange Inside Width:

1.872 inches all flanges

Flange Inside Height:

0.872 inches all flanges

Flange Outside Width:

3.500 inches all flanges

Flange Outside Height:

2.500 inches all flanges

Flange Depth:

0.690 inches all flanges

**Voltage Standing Wave Ratio:** 

1.06

Thready Qty Per Inch (tpi):

20 all flanges all connection facilities

**Maximum Operating Pressure:** 

10.0 pounds per square inch gage

**Waveguide Outside Width:** 

2.000 inches

**Thread Size:** 

0.250 inches all flanges all connection facilities

Waveguide Inside Width:

1.872 inches

Waveguide Inside Height:

0.872 inches

**Waveguide Outside Height:** 

1.000 inches

**Waveguide Longer Offset Distance:** 

8.120 inches

Flange Connecting Facility And Quantity:

8 threaded hole all flanges all connection facilities

## NSN 5985-01-243-0838

Waveguide Assembly - Page 2 of 2



Flange Style:
Contact type all flanges
Waveguide Offset Distance:
7.750 inches
Flexibility:
Flexible single tubing segment
Material:
Beryllium single tubing segment and flange
Style Designator:
Bend type
Thread Series Designator:
Unc all flanges all connection facilities
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

**Fiig:** A073a0