NSN 5985-01-243-0930

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-243-0930

Application Design:
Transmission line
Body Style:
Irregular
Overall Length:
2.560 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
2.360 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.300 inches
Overall Height:
0.850 inches
Overall Width:
2.050 inches
Unthreaded Mounting Hole Diameter:
0.125 inches
End Application:
Drone an/dsm-156a
Coaxial Connector Series Designation:
Sma
Power Rating:
0.01 watts peak
Overall Attenuation Range In Decibels:
+0.0/+60.0
Attenuation Variation Method:
Continuous
Mounting Facility Type And Quantity:
4 unthreaded hole
Frequency Range:
Between 4.000 gigahertz and 8.000 gigahertz
Overall Attenuation Accuracy In Decibels:
-1.00/+1.00
Adjustment Device Type And Quantity:
1 electronic, programmable
Mounting Facility Pattern:
Four position rectangular
Impedance Rating In Ohms:
50.0 input-output
Terminal Type And Quantity:
3 connector, coaxial, female and 3 solder stud
Shalf Life:

N/a

NSN 5985-01-243-0930

Variable Attenuator - Page 2 of 2



	Of			

--

Demilitarization:

No

Fiig:

A223a0