## NSN 5985-01-243-8484

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-243-8484

Application Design:
Transmission line
Body Material:
Steel, corrosion resisting
Body Style:
Err-090
Body Surface Treatment:
Passivated
Overall Length:
Between 0.990 inches and 1.050 inches
Overall Diameter:
0.375 inches
Operating Tempurature Range:
-55.0/+100.0 degrees celsius
End Application:
F-15 aircraft
Voltage Standing Wave Ratio:
1.25
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
Sma
Power Rating:
0.2 kilowatts peak
Rf Signal Attenuation In Decibels:
10.0
Voltage Standing Wave Ratio Frequency Range:
+8.0/+12.4 gigahertz
Attenuation Accuracy Reference Frequency:
12.4 gigahertz
Attenuation Accuracy In Decibels:
-0.50/+0.50
Connection Type Per Function:
Female input and male output
Unpackaged Unit Weight:
0.500 ounces
Mounting Method:
Connector
Terminal Type And Quantity:
2 connector

## NSN 5985-01-243-8484

Fixed Attenuator - Page 2 of 2



Between 8.000 gigahertz and 12.400 gigahertz

**Special Features:** 

Coaxial, resistive film

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A20000